

TM-2-7A-PB0 Torque Motor



Electrical specifications

Winding code : PB0	Symbol	Unit	Water cooling
Continuous torque	T_c	Nm	569
Continuous current	I_c	A_{rms}	20.5
Stall torque	T_s	Nm	468
Stall current	I_s	A_{rms}	16.4
Peak torque(for 1sec.)	T_p	Nm	1140
Peak current(for 1sec.)	I_p	A_{rms}	56
Torque constant	K_t	Nm/Arms	29.62
Electrical time constant	T_e	ms	7
Resistance (line to line at 25°C)	R_{25}	Ω	4.5
Inductance (line to line)	L	mH	31.4
Number of poles	2p		44
Back emf constant (line to line)	K_v	Vrms/rad/s	17.1
Motor constant (at 25°C)	K_m	Nm/ \sqrt{W}	11.42
Thermal resistance	R_{th}	K/W	0.037
Thermal sensor			PTC SNM100+SNM130+Pt1000
Max. DC BUS		V_{DC}	750
Inertia of rotor	J	kgm^2	0.081
Thermal time constant	T_{th}	s	120
Max. continuous power dissipation	P_c	W	4002
Max. peak power dissipation	P_p	W	29870
Rated speed(at 600VDC)		rpm	147

Mechanical specifications

	Symbol	Unit	Water cooling
Mass of rotor	M_r	kg	7.1
Mass of stator	M_s	kg	28.9
Height of stator	H_s	mm	150
Height of rotor	H_r	mm	101
Length of rotor centring fit	H	mm	15
Water temperature difference for P_c	$\Delta\theta$	K	5
Minimum water flow	q	l/min	11.5
Max. pressure drop	Δp	bar	1

T-N curve



Section X-X

General tolerance mm

Nominal dimension	Tolerance
~ 6	±0.1
> 6 ~ 30	±0.2
> 30 ~ 120	±0.3
> 120 ~ 300	±0.4
> 300 ~ 600	±0.5
> 600 ~ 1200	±0.8
> 1200 ~ 2400	±1.0
> 2400	±1.5

#REF!

White Brown

PH U
Pt1000

Green Red

PH W
PH V
PH U

SNM130

Blue Yellow

PH W
PH V
PH U

SNM100

Motor wire table	
Color or wire no.	Signal
U/L1	PH U
V/L2	PH V
W/L3	PH W
Green/Yellow	GND

Except dimensions, all the specifications in the table are in ±10% of tolerance

Version: 2.00

This drawing is only for reference, detail dimensions please refer to approval drawing.

Date: 2020/10/23